

Quote #Click or tap here to enter text.

Equipment/Description	Price USD
GEMINI 12	
Includes:	
4.6hp (3.44kW) industrial-grade integral drive motor. Available voltages:	<mark>]230 VAC / □<b>460VAC</b>,</mark> 3ph, 60hz
Max operating capacity 11.0ft <sup>3</sup> (310 L)	
Textured, straight wall urethane lining	
One (1) set of pop-in drains: Solid, 1/16" (1.5mm), 1/8" (3mm) & 1/4" (6.	<mark>5mm) slots</mark>
Parts separation system with hand lever gate	
One (1) set of urethane-coated separation screens: \$\Bigsig 3/4"\$ (20)	mm) & 🗆 1 ¼" (32mm) openings
Water-driven compound system – 2 to 20 gal/hr (8 to 75 L/hr) flow rate, mixes between	ween 0% and 5%
19 mm socket included for changing eccentric weights	
Integrated lifting eyes	
(denotes factory insta	<b>alled</b> – unless specified on order)

Options	Price USD
☐ On/Off Switch *	\$
☐ Semi-Auto Panel Upgrade *	\$
☐ Special Voltage: (Back Order) ☐ 208VAC / ☐ 575VAC	\$
☐ Manual Closable Drain	\$
☐ Acid Proof Option	\$
☐ Media Classification: includes urethane-coated screen with 1/4" openings	\$
Settling Tank: 30 gal (110 L) cap. with center baffle <sup>1</sup>	
☐ Painted Steel	\$
☐ Stainless Steel	\$
Lift Station: 30 gal (110 L) cap. with center baffle, pumps 100ft (30m) horizontally <sup>2</sup>	
☐ Painted Steel	\$
☐ Stainless Steel	\$
☐ Bolt-On Flexible Fabric Noise Cover <sup>3</sup>	\$
☐ Hanging Flexible Fabric Noise Cover <sup>3</sup>	\$
☐ Free-Standing Rinse Bar <sup>4</sup>	\$
☐ Free-Standing Air Knife <sup>4</sup>	\$
☐ Factory Run Off	\$

Make orders out to:	Shipment: (excluding holidays)
Hammond Roto-Finish	In Stock: 2-3 weeks
C/O Distributor	Back Order: 8-10 weeks

* = Must choose one	Select either only Item <sup>1</sup> or Item <sup>2</sup>
<sup>3</sup> = Pick only one from the set.	<sup>4</sup> = Pick only one from the set.