

Quote #Click or tap here to enter text.

Equipment/Description	Price
USD	
GEMINI 4 FLAT BOTTOM	\$
Includes:	
1.2hp (90kW) industrial-grade integral drive motor. Available voltages:	□230 VAC / □ 460VAC , 3ph, 60hz
Max operating capacity 4.3ft ³ (120 L)	
Textured, straight wall urethane lining	
One (1) set of pop-in drains: ☐solid, ☐1/16" (1.5mm), ☐ 1/8" (3mm) &	□1/4" (6.5mm) slots
Large unload plug	
On/Off control switch (mounted on compound stand)	
Water-driven compound system – 2 to 20 gal/hr (8 to 75 L/hr) flow rate,	mixes between 0% and 5%
19 mm socket included for changing eccentric weights	
Integrated lifting eyes	

Options		Price USD
□ On/Off Switch *	\$	0.00
☐ Semi-Auto Panel Upgrade *	\$	
☐ Special Voltage: (Back Order) ☐208VAC / ☐575VAC	\$	
☐ Manual Closable Drain	\$	
Settling Tank: 30 gal (110 L) cap. with center baffle ¹		
☐ Painted Steel		
☐ Stainless Steel	\$	
Lift Station: 30 gal (110 L) cap. with center baffle, pumps 100ft (30m) horizontally ²		
☐ Painted Steel	\$	
☐ Stainless Steel	\$	
☐ Bolt-On Flexible Fabric Noise Cover ³	\$	
☐ Hanging Flexible Fabric Noise Cover ³	\$	
☐ Factory Run Off	\$	

Make orders out to:	Shipment: (excluding holidays)
Hammond Roto-Finish	In Stock: 2-3 weeks
C/O Distributor	Back Order: 8-10 weeks
* = Must choose one	
Select either only Item ¹ or Item ²	³ = Pick only one from the set.