

Quote #Click or tap here to enter text.

Equipment/Description	Price USD
GEMINI 7	\$
Includes:	
2.9hp (2.2 kW) industrial-grade integral drive motor. Available voltages:	<mark>]230 VAC / □<i>460VAC</i>,</mark> 3ph, 60hz
Max operating capacity 7.0ft <sup>3</sup> (200 L)	
Ribbed, straight wall urethane lining	
One (1) set of pop-in drains: □solid, □1/16" (1.5mm), □1/8" (3mm) & □1/4" (6.	5mm) slots
Parts separation system with hand lever gate	
One (1) set of urethane-coated separation screens:	mm) & 🗆 1 ¼" (32mm) openings
Water-driven compound system – 2 to 20 gal/hr (8 to 75 L/hr) flow rate, mixes bet	ween 0% and 5%
19 mm socket included for changing eccentric weights	
Integrated lifting eyes	
(denotes factory de	<b>fault</b> – unless specified on order)

ptions		Price USD
☐ On/Off Switch *		\$
☐ Semi-Auto Panel Upgrade *		\$
☐ Special Voltage: (Back Order)	□208VAC / □575VAC	\$
☐ Manual Closable Drain		\$
☐ Acid Proof Option		\$
☐ Media Classification: includes urethane-coated screen with 1/4" openings		\$
Settling Tank: 30 gal (110 L) cap. with center baffle <sup>1</sup>		
☐ Painted Steel		\$
☐ Stainless Steel		\$
ift Station: 30 gal (110 L) cap. with center baffle, pumps 1	.00ft (30m) horizontally <sup>2</sup>	
☐ Painted Steel		\$
☐ Stainless Steel		\$
☐ Bolt-On Flexible Fabric Noise Cover <sup>3</sup>		\$
☐ Hanging Flexible Fabric Noise Cover <sup>3</sup>		\$
☐ Free-Standing Rinse Bar <sup>4</sup>		\$
☐ Free-Standing Air Knife <sup>4</sup>		\$
☐ Factory Run Off		\$

Make orders out to:	Shipment: (excluding holidays)
Hammond Roto-Finish	In Stock: 2-3 weeks
C/O Distributor	Back Order: 8-10 weeks
* = Must choose one	Select either only Item <sup>1</sup> or Item <sup>2</sup>
<sup>3</sup> = Pick only one from the set.	<sup>4</sup> = Pick only one from the set.

1600 Douglas Avenue • Kalamazoo, Michigan 49007

(269) 345-7151 • www.hammondroto.com

Formatted: Spanish (Spain)