

BELT GRINDING MACHINES

ABRASIVE BELT & BRUSH FINISHING EQUIPMENT



Front View



Top Cover of Platen in Open Position

Hammond **ROTO FINISH**

HAMMOND BELT GRINDING

Specifications

MODEL	Length mm (in.)	Width mm (in.)	Height mm (in.)	Belt Width mm (in.)	Belt Length mm (in.)	Motor Horse Power kw (HP)	SPFM rpm	460 Volts Amp Load	230 Volts Amp Load	Aprox Shipping Weight kg (lbs.)
K-3000	1320 (52)	483 (19)	1016 (40)	76.2 (3)	2489.2 (98)	2.05 (5.5)	9000	8.7	17.4	115 (310)

MODEL	Length mm (in.)	Width mm (in.)	Height mm (in.)	LOS Belt Width mm (in.)	LOS Belt Length mm (in.)	SA-12 Belt Width mm (in.)	SA-12 Belt Length mm (in.)	Motor Horse Power kw (HP)	SPFM LOS Heads rpm	SPFM LOS Heads rpm	460 Volts Amp Load	230 Volts Amp Load	Aprox Shipping Weight kg (lbs.)
UBG-132	1397 (55)	458 (18)	1016 (40)	76.2 (3)	3353 (132)	76.2 (3)	3760 (148)	1.47 (2)	5500	2300	2.8	5.6	112 (300)

UNIVERSAL BELT GRINDING Specifications

	Length mm (in.)	Width mm (in.)	Height mm (in.)	Belt Width mm (in.)	Belt Length mm (in.)	Wheel Diameter mm (in.)	Wheel Width mm (in.)	Motor Horse Power kw (HP)	SPFM rpm	460 Volts Amp Load	230 Volts Amp Load	Aprox Shipping Weight kg (lbs.)
UBG-62-65	838 (33)	787 (31)	1676 (66)	63.5 (2.5)	1530 (60)	N/A	N/A	1.47 (2)	5500	2.8	5.6	127 (340)
UBG-62-65*	939 (37)	838 (33)	1676 (66)	63.5 (2.5)	1530 (60)	N/A	N/A	1.47 (2)	5500	2.8	5.6	168 (450)
UBG-8-65	838 (33)	787 (31)	1676 (66)	63.5 (2.5)	1530 (60)	203 (8)	63.5 (2.5)	1.47 (2)	5500	2.8	5.6	127 (340)

The **UBG Series of Belt Grinders**, manufactured by Hammond Roto-Finish are a heavy-duty, built-to-last product. A wide variety of configurations are available.

